

**Sling Specifications & Dimensions**  
**Eye-to-Eye Double Play Polyester Webbing**

Model	Capacity (lbs)	L Length (ft)	W Width (in)	Weight (lbs)
WSDP-020	2,200	4	2	1
		6		2
		8		2
		10		2.5
		12		2.5
		14		3
		16		3
		18		3.5
WSDP-040	4,400	4	2.25	1
		6		2
		8		2
		10		3
		12		3.5
		14		3.5
		16		3.5
		18		4
WSDP-060	6,600	4	3	3
		6		4
		8		4
		10		5
		12		6
		14		6
		16		6
		18		7
WSDP-080	8,800	4	4	3
		6		4
		8		5
		10		6
		12		7
		14		7
		16		7
		18		9
WSDP-100	11,000	4	5	4
		6		5
		8		6
		10		8
		12		9
		14		9
		16		9
		18		10



**Endless / Round Single-Ply Polyester Webbing Specifications & Dimensions**

Model	Capacity (lbs)	L Length (ft)	W Width (in)	Weight (lbs)
WSESP-020	2,200	4	1	1
		6		1
		8		1
		10		1
		12		1
		14		1
		16		1
		18		1
WSESP-040	4,400	4	2	1
		6		1
		8		1.5
		10		2
		12		2
		14		2
		16		2
		18		3
WSESP-060	6,600	4	3	1.5
		6		2
		8		2
		10		3
		12		4
		14		5
		16		5
		18		6
WSESP-080	8,800	4	4	3
		6		3
		8		4
		10		5
		12		6
		14		7
		16		8
		18		10



**Endless / Round Double-Ply Polyester Webbing**

Model	Capacity (lbs)	L Length (ft)	W Width (in)	Weight (lbs)
WSEDP-040	4,400	4	1	1
		6		1
		8		1
		10		1
		12		1
		14		1
		16		1
		18		1
WSEDP-060	6,600	4	2	2
		6		3
		8		4
		10		4.5
		12		5
		14		7
		16		9
		18		11
WESEDP-080	8,800	4	3	3
		6		4
		8		5
		10		6
		12		7
		14		7
		16		7
		18		8

**Round Rope Slings Specifications & Dimensions**

Model	Capacity (lbs)	L Length (ft)	W Weight (lbs)
RS-020	2,200	4	0.8
		6	1.2
		8	1.6
		10	2
		12	2.4
		14	2.8
		16	3.2
		18	3.6
RS-050	5,500	20	4
		4	1.2
		6	1.8
		8	2.4
		10	3
		12	3.6
		14	4.2
		16	4.8
RS-080	8,800	18	5.4
		20	6
		4	2
		6	3
		8	4
		10	5
		12	6
		14	7
RS-100	11,000	16	8
		18	9
		20	10
		4	3
		6	4.5
		8	6
		10	7.5
		12	9
RS-100	11,000	14	10.5
		16	12
		18	13.5
		20	15

RS-130	13,000	4	3.4
		6	5.1
		8	6.8
		10	8.5
		12	10.2
		14	11.9
		16	13.6
		18	15.3
		20	17
RS-210	21,000	6	7.5
		8	10
		10	12.5
		12	15
		14	17.5
		16	20
		18	22.5
		20	25
RS-250	25,000	6	8.7
		8	11.6
		10	14.5
		12	17.4
		14	20.3
		16	23.2
		18	26.1
		20	29
RS-900	60,000	10	41
		12	49.2
		14	57.4
		16	65.6
		18	73.8
		20	82