



Slings

Model RS



Features

- Capacity range from 1 to 40 Tons
- High strength to weight ratio
- Low elongation / extreme flexibility
- Double cover for extra life
- Polyester interior fibers do not contact the load, meaning little wear as long as cover is intact
- Long lasting tag indicates working load limits

Sling Construction




The slings are designed for lifting loads. Before using, make sure that the load doesn't exceed the rated capacity of the sling. Slings should always be stored indoors.



689 S.W. 7th Terrace
Dania, FL 33004
Phone: (954) 367-6116
www.acihoist.com

Model	Capacity (lbs)	L Length (ft)	Weight (lbs)
RS-020	2,200	4	0.8
		6	1.2
		8	1.6
		10	2
		12	2.4
		14	2.8
		16	3.2
		18	3.6
RS-050	5,500	20	4
		4	1.2
		6	1.8
		8	2.4
		10	3
		12	3.6
		14	4.2
		16	4.8
RS-080	8,800	18	5.4
		20	6
		4	2
		6	3
		8	4
		10	5
		12	6
		14	7
RS-100	11,000	16	8
		18	9
		20	10
		4	3
		6	4.5
		8	6
		10	7.5
		12	9
RS-130	13,000	14	10.5
		16	12
		18	13.5
		20	15
		4	3.4
		6	5.1
		8	6.8
		10	8.5
		12	10.2
		14	11.9
		16	13.6
		18	15.3
		20	17

RS-210	21,000	6	7.5
		8	10
		10	12.5
		12	15
		14	17.5
		16	20
		18	22.5
		20	25
RS-250	25,000	6	8.7
		8	11.6
		10	14.5
		12	17.4
		14	20.3
		16	23.2
		18	26.1
		20	29
RS-900	60,000	10	41
		12	49.2
		14	57.4
		16	65.6
		18	73.8
		20	82

Capacities			
Model			
	Vertical (lbs)	Choked (lbs)	Basket (lbs)
Round Slings			
RS-020	2,600	2,080	5,200
RS-050	5,300	4,240	10,600
RS-080	8,400	6,720	16,800
RS-100	10,600	8,480	21,200
RS-130	13,200	10,560	26,400
RS-210	21,200	16,960	42,400
RS-250	25,000	20,000	50,000
RS-900	90,000	72,000	180,000