






Features

- Capacity Range: 2,200 to 11,000 lbs.
- Double-Ply polyester webbing sling with reinforced lifting eyes.
- Suitable in applications where minimal damage to the load's surface finish is important.
- Compact size and light weight.
- Color coded according to DIN-EN-1492-1.
- Each inch webbing width is equal to 1 Ton capacity.
- The flat cross section makes it easy to be removed from beneath the load once it has been placed.
- Safety factor 7:1.

Sling Design

This double-ply polyester webbing sling has reinforced lifting eyes. It is a popular, versatile sling adaptable for vertical hitch, choker hitch, and basket hitch. It is comprised of flat loop eyes formed of polyester and oriented in the same plane as the sling body. The sling legs can be spread for improved load balance and choke tightly around loads.

Dimensions & Specifications

		Capacities (lbs)				
Color	Model Number				Width (in)	Length (ft)
		Vertical (lbs)	Choked (lbs)	Basket (lbs)		
Eye & Eye Polyester Slings						
Purple	WSDP-020	2,200	1,800	4,400	2.00	4'-18'
Green	WSDP-040	4,400	3,500	8,800	2.25	4'-18'
Yellow	WSDP-060	6,600	5,300	13,200	3.00	4'-18'
Gray	WSDP-080	8,800	7,000	17,600	4.00	4'-18'
Red	WSDP-100	11,000	8,800	22,000	5.00	4'-18'

* These items are kept in inventory and, in most cases, are ready for immediate shipment.

Last updated: 2013

Please Note: The slings are designed for lifting loads. Before using, make sure that the load doesn't exceed the rated capacity of the sling. Slings should always be stored indoors.