






Features

- Capacity Range: 2,200 to 8,800 lbs.
- Available in Single or Double Ply.
- Lightweight and durable. Able to withstand acid, bleaching agents, and high temperatures.
- Color coded according to DIN-EN-1492-1.
- Safety factor 7:1.
- The lift weight, flexibility, and stretch of synthetic slings reduces fatigue and strain on riggers.
- It is economical and adaptable with uses in all hitch arrangements.

Sling Design

Endless type slings are one of the most versatile and widely used types because of their adaptability to numerous applications. Lightweight and extremely flexible; they are easily and quickly handled and adjusted to the load. Sling life is prolonged because of the rotation of the wear surfaces. Single and double ply thicknesses are available.

Dimensions & Specifications

Color	Model Number	Capacities (lbs)			Width (in)	Length (ft)
		 Vertical (lbs)	 Choked (lbs)	 Basket (lbs)		
Endless Single-Ply Polyester Webbing Slings						
Purple	WSESP-020	2,200	1,800	4,400	2	4'-18'
Green	WSESP-040	4,400	3,500	8,800	2.25	4'-18'
Yellow	WSESP-060	6,600	5,300	13,200	3	4'-18'
Gray	WSESP-080	8,800	7,000	17,600	4	4'-18'
Endless Double-Ply Polyester Webbing Slings						
Purple	WSEDP-040	4,400	3,500	8,800	2	4'-18'
Green	WSEDP-060	6,600	5,300	13,200	2.25	4'-18'
Gray	WSEDP-080	8,800	7,000	17,600	2.25	4'-18'

* These items are kept in inventory and, in most cases, are ready for immediate shipment.

Last updated: 2013

Please Note: The slings are designed for lifting loads. Before using, make sure that the load doesn't exceed the rated capacity of the sling. Slings should always be stored indoors.